Bowers & Wilkins

Custom Installation CWM8.3 D





Bowers & Wilkins

www.bowers-wilkins.com

Copyright © B&W Group Ltd. E&OE Flowport, FST and Nautilus are trademarks of B&W Group Ltd.

See nothing, hear everything

CWM8.3 D is a three-way in-wall loudspeaker, conceived to offer the very best performance for a customer requiring great sound without seeing the source.

It features a decoupled Diamond dome tweeter, a 5in Continuum FST midrange drive unit and two 7in Aerofoil low-frequency drivers.

The central baffle is rotatable, so CWM8.3 D can be used in either vertical or horizontal alignment.

For optimum discretion when installed, the Continuum cone is given a dark finish.

Technical Specifications

Description 3-way in-wall loudspeaker

Technical features Aluminium mini baffle can be

turned through 90 degrees
Diamond Dome, Nautilus™

tube-loaded tweeter Anti-resonance plug

Flowport™

FST™ midrange unit

Carbon Aerofoil bass drivers

Drive units 1x Ø25mm (1in) Diamond Dome, Nautilus™

tube-loaded tweeter

1x ø130mm (5in) Continuum midrange driver

2x ø180mm (7in) Aerofoil Bass drivers

Frequency range (-6dB) 30Hz - 35kHz

Recommended

Amplifier Power 200W

Sensitivity 89dB

Nominal Impedance 8Ω

Frame height 880mm (34.6in)

Frame width 254mm (10in)

Cut-out height 864mm (34in)

Cut-out width 238mm (9.4in)

Protrusion 8mm (0.3in)

Net weight 10.9kg

Back Box BB CWM8.3

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specifications.