## *CDM*™*SNT*

## Wall-mount loudspeaker

## **Product Summary**

- The CDM SNT combines practicality and elegance with an array of technological features.
- Practically designed with its shallow profile and contoured cabinet edges the speaker can
  easily be mounted to a wall with the compact bracket which is supplied and fitted to the rear
  of the speaker.
- Available in a choice of real wood veneers to compliment the rest of the CDM NT range.

## Technical highlights

Nominal impedance 8 (min 4.8 )



Nautilus™ Tweeter: B&W's Nautilus™ Tweeter technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Description 50W - 120W into 8 ohm on unclipped 2-way closed-box system Power handling Drive units 1 x 25mm alloy dome high-frequency programme 1 x 165mm woven Kevlar® cone Dimensions Height: 394mm Width: 392mm bass/midrange Frequency response 75Hz – 20kHz ± 3dB on reference Finishes Cabinet: Real wood veneers, Black Ash, Cherrywood, Red Stained Cherrywood axis Sensitivity 90dB spl (2.83V, 1m) Grilles: Black cloth

