CDM™CNT

Magnetically shielded centre channel loudspeaker system

Product Summary

- The magnetically shielded CDM CNT centre channel loudspeaker completes the CDM NT range.
- Like the rest of the speakers in the CDM NT family, the centre channel harnesses all the latest technological advancements such as Nautilus™ tweeter, Kevlar® and contoured cabinet edges.

Technical highlights



Nautilus[™] Tweeter: B&W's Nautilus[™] Tweeter technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Flowport™: Golf ball aerodynamics theory points the way towards lower distortion reflex ports. Dimples improve the way the air flows over the surface of any object. In the case of reflex ports, they offer a significant improvement over simply flaring the port ends in reducing air flow turbulence at each end of the port; so you get less chuffing noise and less compression at high sound levels.

Description	2-way vented-box system with magnetic	Nominal impedance	8Ω (min 4.6Ω)
	shielding	Power handling	50W - 120W into 8 ohm on unclipped
Drive units	1 x 25mm alloy dome high-frequency		programme
	1 x 165mm woven Kevlar® cone	Dimensions	Height: 300mm Width: 460mm
	bass/midrange		Depth: 290mm
Frequency response	50Hz - 20kHz ± 3dB on reference	Finishes	Cabinet: Real wood veneers, Black Ash,
	axis		Cherrywood, Red Stained Cherrywood
Sensitivity	91dB spl (2.83V, 1m)		Grilles: Black cloth



