



See nothing, hear everything

The CWM 6260 is an in-wall speaker distinguished by its adjustable level 25mm (1 in) soft dome tweeter. It brings smoother and more detailed high frequency performance to a package that also includes a woven glass fibre 165mm (6½ in) bass/midrange driver and three-position switchable high frequency equalisation. Installation simplicity is catered for by a simple and effective integrated swing out dog fixing chassis. The CWM 6260 is an elegantly engineered and cost effective route to high quality in-wall sound.

Technical Specification

Technical features	Adjustable level soft dome tweeter Three position EQ switch Swing-out dog fixings
Description	2-way in-wall speaker system
Drive units	1x ø25mm (1 in) soft dome high-frequency 1x ø165mm (6.5 in) glassfibre mid/bass
Frequency range	-6dB at 40Hz and 30kHz
Frequency response	50Hz-22kHz ±3dB on reference axis
Sensitivity	89dB spl (2.83V, 1m)
Nominal impedance	8Ω (minimum 3.6Ω)
Crossover frequency	3.2kHz
Recommended amplifier power	20W - 130W continuous into 8Ω on unclipped programme
Frame size	Height: 310mm (12.2 in) Width: 216mm (8.5 in)
Cut-out size	Height: 281mm (11.1 in) Width: 186mm (7.3 in)
Min depth req	93mm (3.7 in) from wall surface
Net weight	1.6kg (3.5lb)
Finish	Semi-matt white suitable for customising or pre-painting (paint mask included)
Accessories	Pre-mount kit for new construction (PMK 650)



CWM 6260

Architectural and Engineering Specifications

The loudspeaker system shall be of the mono-amped 2-way type comprising of a single flush mountable rectangular enclosure containing one 6.5in bass-mid driver with woven glass fibre cone and one 1in textile dome tweeter, with 3 position EQ switch.


Performance specifications of a typical production unit shall meet or exceed the following:

Frequency response shall be 50 – 22kHz. Nominal impedance shall be 8 Ohm. Total power handling shall be 130W continuous into 8 Ohm on unclipped programme. Sensitivity measured with 2.83V at 1-meter distance on axis, mean averaged between 50 – 22kHz shall be 89dB.


External dimensions shall be 310mm (12.2in) height x 216mm (7.4in) width x 96.5mm (3.8in) depth. Total weight shall be 2.1kg (4.7lb).

The loudspeaker system shall be the B&W CWM 6260. No other system shall be acceptable unless the above combined performance are equalled or exceeded.


Polar Response Horizontal




Polar Response Vertical



Frequency Response



Dimensions



B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk

Copyright © B&W Group Ltd. E & OE.
B&W Group Ltd reserves the right to amend details of the specifications
without notice in line with technical developments.