



Bowers & Wilkins

HTM82 D5

Technical Information



Technical features

Diamond dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST™ midrange
Anti-Resonance plug
Biomimetic Suspension
Matrix™
Aerofoil™ bass cones
Flowport™

Description

3-way vented-box system

Drive units

1× ø25mm (1in) Diamond dome high-frequency
1× ø130mm (5in) Continuum™ cone FST™ midrange
2× ø165mm (6.5in) Aerofoil™ bass

Frequency range

-6dB 33Hz–35kHz

Frequency response

(+/-3dB from reference axis)

45Hz–28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

89dB

Harmonic distortion

2nd and 3rd harmonics (89dB, 1m on axis)
<1% 80Hz – 20kHz
<0.3% 100Hz – 8kHz

Nominal impedance

8Ω (minimum 3.0Ω)

Recommended amplifier power

50W–200W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 289mm (11.4in) including tweeter
Width: 715mm (28.1in) cabinet only
Depth: 363mm (14.3in) including grille
and terminals

Net weight

26.1kg (57.5lbs)

Finishes

Cabinet: Dark Walnut
Stealth Black
Warm White
Grille: Black (Stealth Black, Dark Walnut)
Grey (Warm White)

Accessories

FS-HTM stand: Black
Titanium

HTM82 D5

Technical Information

bowerswilkins.com