

CDM™1SE

Stand-mount/Bookshelf loudspeaker system

Product Summary

- Braced cabinet construction dramatically reduces cabinet resonance by adding the twin virtues of strength and rigidity to the cabinet walls. Gold-plated terminals permit bi-wiring or bi-amplification.
- Having the tweeter separate from the main cabinet readily allows it to be set back and time aligned with the acoustic centre of the bass/midrange cone, which is located behind the plane of the front baffle, and minimises the effects of diffraction from the cabinet edges. This results in improved imaging and coherence.

Technical highlights

- B&W's Tweeter on top technology ensures that the sound remains focused and time-sensitive and that the stereo image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Recommended by Hi-Fi Choice
April 1998



Awarded What Hi-Fi's prestigious
five stars. February 1998



Description	2-way vented-box system	Power handling	30W · 120W into 8 ohm on unclipped programme
Drive units	1 x 25mm alloy dome high-frequency 1 x 165mm woven Kevlar® cone bass/midrange	Dimensions	Height: 370mm Width: 220mm Depth: 274mm
Frequency response	58Hz – 20kHz ± 3dB on reference axis	Finishes	Cabinet: Real wood veneers, Red Ash, Black Ash, Cherry Grilles: Black cloth
Sensitivity	88dB spl (2.83V, 1m)		
Nominal impedance	8 (min 4.5)		



LISTEN AND YOU'LL SEE