



Bowers & Wilkins

802 D5

Technical Information



Technical features

Diamond dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST™ midrange
Anti-Resonance plug
Biomimetic Suspension
Turbine Head
Matrix™
Aerofoil™ bass cones
Flowport™

Description

3-way vented-box system

Drive units

1× ø25mm (1in) Diamond dome high-frequency
1× ø150mm (6in) Continuum™ cone FST™ midrange
2× ø200mm (8in) Aerofoil™ bass



Frequency range

-6dB 14Hz–35kHz

Frequency response

(+/-3dB from reference axis)

17Hz–28kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

90dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 70Hz – 20kHz
<0.3% 100Hz – 8kHz

Nominal impedance

8Ω (minimum 3.3Ω)

Recommended amplifier power

50W–500W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 1218mm (48.0in)
including tweeter and plinth

Width: 345mm (13.6in) cabinet only
413mm (16.2in) including plinth

Depth: 556mm (21.9in) including grille
and terminals
589mm (23.2in) including plinth



Net weight

91.4kg (201.4lbs)

Finishes

Cabinet: Stealth Black
Warm White
Light Walnut
Dark Walnut

Grille: Black (Stealth Black and Dark Walnut)
Grey (Warm White and Light Walnut)



802 D5

Technical Information

bowerswilkins.com