



## See nothing, hear everything

Designed for wall-mounted left, centre and right speaker positions in a discreet home cinema system, CWM7.4 S2 can also be mounted beside, above or below the screen, ensuring crystal-clear dialogue and dramatic special effects. Thanks to Bowers & Wilkins unique QuickDogs™ fixing method, installation is simple, requiring no tools. Its 2.5-way configuration features a single Carbon Dome tweeter, twin 100mm (4in) Continuum cone midrange units and twin 100mm (4in) Aramid Fibre/paper bass cones.

### Technical Specifications

<b>Technical features</b>	Carbon Dome tweeter Continuum midrange Aramid Fibre/Paper bass cones
<b>Description</b>	2½-way in-wall system
<b>Drive units</b>	1x ø25mm (1 in) Carbon Dome high-frequency 2x ø100mm (4 in) Continuum cone mid/bass 2x ø100mm (4 in) Aramid Fibre/Paper profile bass
<b>Frequency range (-6dB)</b>	-6dB at 43Hz - 33kHz
<b>Frequency Response -3dB</b>	45Hz - 28kHz ±3dB
<b>Sensitivity</b>	86dB spl (2.83Vrms, 1m)
<b>Harmonic distortion</b>	2nd and 3rd harmonics (90dB, 1m) <1% 80Hz - 33kHz <0.5% 120Hz - 33kHz
<b>Nominal impedance</b>	8Ω (minimum 4.9Ω)
<b>Recommended amplifier power</b>	25W - 150W into 8Ω on unclipped programme
<b>Frame height</b>	625mm (24.6in)
<b>Frame width</b>	175mm (6.9in)
<b>Depth (behind surface)</b>	92.5mm (3.64in)
<b>Cut-out height</b>	599mm (23.6in)
<b>Cut-out width</b>	149mm (5.9in)
<b>Protrusion</b>	8mm (0.3in)
<b>PMK</b>	PMK CWMC7
<b>Net weight</b>	6.2kg (13.73 lb)
<b>Finishes</b>	Grille: White

