## Bowers & Wilkins

## Custom Installation CWM8.5 D





CWM8.5 D is a two-way in-wall loudspeaker. It offers exceptionally high performance from a compact loudspeaker.

It features a decoupled Diamond dome tweeter and a single 7inch bass/mid Continuum driver with anti-resonance plug.

For optimum discretion when installed, the Continuum cone is given a dark finish.

## **Technical Specifications**

Description	2-way in-wall loudspeaker
Technical features	Diamond Dome, Nautilus™ tube-loaded tweeter Anti-resonance plug Flowport™
Drive units	1x ø25mm (1in) Diamond Dome, Nautilus™ tube-loaded tweeter 1x ø180mm (7in) Continuum cone bass/ midrange driver with anti-resonance plug
Frequency range (-6dB)	35Hz - 35kHz
Recommended Amplifier Power	120W
Sensitivity	89dB
Nominal Impedance	8Ω
Frame height	411mm (16.2in)
Frame width	247mm (9.7in)
Cut-out height	395mm (15.5in)
Cut-out width	231mm (9.1in)
Protrusion	8mm (0.3in)
Net weight	3.5kg
Back Box	BB CWM8.5



www.bowers-wilkins.com

Copyright © B&W Group Ltd. E&OE Flowport, FST and Nautilus are trademarks of B&W Group Ltd.