CDM™9NT

Floor-standing loudspeaker system

Product Summary

- The CDM 9NT is the largest floorstander in the range producing generous bass
 extension and delivering a tight midrange. The CDM 9NT incorporates the unique
 surroundless midrange FST first pioneered in the 800 Series. Technological features
 include Nautilus tweeter, braced cabinet construction, Flowport and mushroom dust cap
 for improved bass throw.
- The handcrafted cabinets in real wood finishes incorporate the best in design knowhow; the styling and contouring is truly a triumph in the collaboration between science and nature.

Technical highlights



Tweeter on top: B&W's Tweeter on top technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&WV developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Flowport™: Golf ball aerodynamics theory points the way towards lower distortion reflex ports. Dimples improve the way the air flows over the surface of any object. In the case of reflex ports, they offer a significant improvement over simply flaring the port ends in reducing air flow turbulence at each end of the port; so you get less chuffing noise and less compression at high sound levels.

4	1		
1	1	П	
		ı	
	4	ı	
)))	ı	
6			
)))]		
	1/1		
400			
1			

Description	3-way vented-box system	Nominal impedance	8Ω (min 3.0Ω)
Drive units	1 x 25mm alloy dome high-frequency	Power handling	50W - 200W into 8 ohm on
	1 x 165mm woven Kevlar® cone		unclipped programme
	FST™ midrange	Dimensions	Height: 1000mm Width: 220mm
	2 x 165mm paper/Kevlar® cone bass		Depth: 315mm
Frequency response	$38Hz - 20kHz \pm 3dB$ on reference	Finishes	Cabinet: Real wood veneers, Black Ash,
	axis		Cherrywood, Red Stained Cherrywood
Sensitivity	90dB spl (2.83V, 1m)		Grilles: Black cloth

