

# CDM 1


## Stand-mount/Bookshelf loudspeaker system

### Product Summary

- Designed for shelf or stand, the compact dimensions of the CDM 1 give no clue to the enormity of the studio-quality sound which it is capable of producing. This was acknowledged by the fact that not long after the launch the Eisa Association awarded the CDM 1 the European Loudspeaker of the Year.
- Braced cabinet construction dramatically reduces cabinet resonance by adding the twin virtues of strength and rigidity to the cabinet walls. Gold-plated terminals permit bi-wiring or bi-amplification.

### Technical highlights

- B&W's Tweeter on top technology ensures that the sound remains focused and time-sensitive and that the stereo image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



European High End Audio of the Year  
1995  
EISA Awards



Awarded What HiFi's prestigious  
five stars. December 1995



<b>Description</b>	2-way 4th-order vented-box system	<b>Power Handling</b>	30W - 120W into 8 ohms on unclipped programme
<b>Drive Units</b>	1 x 25mm (1in) alloy dome - high frequency 1 x 165mm (6.5in) kevlar® - bass/mid-range	<b>Dimensions</b>	Height: 370mm Width: 220mm Depth: 274mm
<b>Frequency Response</b>	64Hz - 20Hz ±2dB on reference axis	<b>Net Weight</b>	8.5kg
<b>Sensitivity</b>	88dB spl (2.83V 1m)	<b>Finish</b>	Cabinet: Real Wood Veneers, Black Ash, Cherrywood, Red Ash Grille: Black Cloth
<b>Nominal Impedance</b>	8 ohms (minimum 4.5 ohms)		



LISTEN AND YOU'LL SEE