DM560

Stand-mount/Bookshelf loudspeaker system

Product Summary

The two way front vented system encompasses the same design technology of the DM550
with its rigid one-piece baffle construction, but offers a noticeable extended bass – thanks to
a bigger 8in bass/midrange driver and increased enclosure size.

Technical highlights

- B&W's Tweeter technology ensures that the sound remains focused and time sensitive and that the stereo image is presented with unparalleled three dimensional accuracy.
- The cabinets feature a specially designed high density front baffle which achieves almost
 Matrix-like stability in strengthening overall enclosure construction. The bevel edges of the front
 moulding reduce diffraction and improve dispersion.
- The crossover components use heavy gauge wire throughout and new drivers guarantee not only high reliability but ensure that top specifications are met.



Drive Units	1 x 26mm high-frequency with	Sensitivi
	aluminium dome, 26mm coil on	Nomina
	aluminium dome former, wound with	Power H
	polymide resin and heat cured	
	1 x 200mm bass/midrange with	Dimensi
	composite short fibre cone, 26mm coil	
	on high temperature former, wound with	Finish
	polymide resin and heat cured	

Frequency Response 65Hz – 20kHz ± 2.5dB on reference axis

ensitivity 90dB spl(2.83V 1m)
Iominal Impedance 8 ohms

Power Handling 10W - 75W into 8 ohms on

unclipped programme

mensions Height: 490mm Width: 236mm

Depth: 302mm

Black ash or walnut vinyl

