



Bowers & Wilkins

804 D5

Technical Information

**Technical features**

Diamond dome tweeter
 Solid Body Tweeter-on-Top
 Continuum™ cone FST™ midrange
 Anti-Resonance plug
 Biomimetic Suspension
 Matrix™
 Aerofoil™ bass cones
 Flowport™

Description

3-way vented-box system

Drive units

1 × ø25mm (1in) Diamond dome high-frequency
 1 × ø130mm (5in) Continuum™ cone FST™ midrange
 2 × ø165mm (6.5in) Aerofoil™ bass

Frequency range

-6dB 20Hz–35kHz

Frequency response

(+/-3dB from reference axis)

19Hz–24kHz ±3dB

Sensitivity

(on axis at 2.83Vrms at 1m)

89dB

Harmonic distortion

2nd and 3rd harmonics (90dB,1m on axis)
 <1% 90Hz – 20kHz
 <0.3% 120Hz – 8kHz

Nominal impedance

8Ω (minimum 3.0Ω)

Recommended amplifier power

50W–1000W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 1101mm (43.3in)
 including tweeter and plinth

Width: 238mm (9.4in) cabinet only
 308mm (12.1in) including plinth

Depth: 337mm (13.3in) cabinet only
 392mm (15.4in) including grille
 and terminals

Net weight

40.3kg (88.7lbs)

Finishes

Cabinet: Stealth Black
 Warm White
 Light Walnut
 Dark Walnut

Grille: Black (Stealth Black and Dark Walnut)
 Grey (Warm White and Light Walnut)

