



The SCMS features essentially the same driver complement as the 805S. It's a 2-way system with a Kevlar® cone bass / midrange driver and aluminium dome tweeter. Here, though, the cabinet is much shallower so that it can be mounted on-wall with the minimum of intrusion into the living space. The system is also balanced for its intended on-wall application, taking into account the bass reinforcement from the rear wall.

The system comes complete with a custom wall bracket that allows angular adjustment in both horizontal and vertical planes. This allows the speaker to be angled towards the listeners or, if preferred for a more diffuse surround sound field, away from the listening area.

The SCMS is ideal for use as a stereo front speaker or as a rear surround. To give a more discreet aspect when the speaker is mounted high on the wall for surround applications, the tube-loaded tweeter has been brought into the main cabinet, rather than being mounted on top.

Description: 2-way vented-box system

Frequency Range: -6dB at 48Hz and 50kHz

Frequency Response: 60Hz – 22kHz ±3dB on reference axis

Sensitivity: 88dB spl (2.83V, 1m)

Nominal Impedance: 8Ω (minimum 4.7Ω)

Dimensions: H 399mm W 373mm D 219mm
H 15.7" W 14.7" D 8.6"
(not including wall bracket)

Weight: 8.5 kg / 19 lbs.

Finishes: Cherrywood, Rosenut, Black Ash

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk