



See nothing, hear everything

The CWM7.4 features a 150mm (6in) bass/mid-range driver set in a die-cast chassis and a Nautilus™ tube loaded 25mm (1in) soft dome tweeter. With a critically formed baffle constructed from glass reinforced ABS, the speaker features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound. Utilising the best quality components, such as having Mundorf components on the crossover, combined with proven technologies such as Flowport™ ensures that this speaker provides impressive sound reproduction.

Technical Specifications

Description	2-way in-wall system
Drive units	1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter 1x ø150mm (6in) blue aramid fiber cone bass/midrange
Frequency Range (-6dB)	47Hz – 28kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	89dB
Impedance Nominal (min)	6Ω (5Ω)
Frame height	415mm (16.5in)
Frame width	251mm (10in)
Cut-out height	395mm (15.6in)
Cut-out width	232mm (9.1in)
Reservoir box height	460mm (18.1in)
Reservoir box width	220mm (8.7in)
Reservoir box depth	60mm (2.4in)
Depth behind surface	90mm (3.6in)
Protrusion	6.5mm (0.25in)
PMK	7.4W